Charlie out

Easy joy!

LIRALIGHTING Enjoy Our Light

Easy to install, surface mounted downlight. The luminaire body is made of aliminum. Two light distribution angles 60° and 90° to choose from. The luminaire can be treated interchangeably with luminaires for compact fluorescent lamps. Application: in passageways, conference rooms, shop displays, office buildings.

CE IP44







general data	
luminaire body	aluminum
mounting type	surface-mounted
ingress protection IP	44
operation temperature range	from -20°C to +40°C
lifetime L80B10	50 000h
electrical data	
nominal voltage	220-240V AC
nominal frequency	50-60Hz
protection class	I
contains light source	yes
connection	connector through
dimming	none
lighting data	
light source	LED
colour rendering index	CRI>80
tolerance of luminous flux	+/-10%
optical data	
optical system	highly polished reflector
material	aluminum
light emission	direct
light distribution	symmetrical
beam angle	60° / 90°

code	power [W]	luminaire power [W]	luminaire flux [lm]	luminaire efficacy [lm/W]	diameter [mm]	height [mm]	weight [kg]	box [mm]
E1037.K.C.L	27	30	3180	106	235	180	1,0	250x250x200

K-colour temperature

03 — 3000K

04 — 4000K

C-standard colour

03 — white biały

05 — black czarny

06 — light grey jasny szary

L-beam angle

60 — 60°

90 — 90°

We reserve the right to withdraw and change products from the catalogue at any time without prior notice. The colour options presented in the catalogue may differ from the actual ones. Technical parameters are subject to change.

Liralighting Sp. zo. o. | ul. Saperów 4 | 82-300 Elbląg | info@liralighting.pl |tel. +48 55 236 11 85 | fax. +48 55 232 65 89 | www.liralighting.pl