Jerry

Easy joy!

LIRALIGHTING Enjoy Our Light

The construction of the Jerry luminaire is based on an aluminum profile. The applied opal diffuser evenly diffuses the light along its surface. It is perfect for offices or reception areas. The luminaires are available in surface mounted and suspended version.

CE IP20





general data	
luminaire body	aluminum
mounting type	surface-mounted
ingress protection IP	20
operation temperature range	from -20°C to +40°C
lifetime L80B10	50 000h
electrical data	
nominal voltage	220-240V AC
nominal frequency	50-60Hz
protection class	I
contains light source	yes
connection	connector through
dimming	none (options: DALI)
lighting data	
light source	LED
colour rendering index	CRI>80
tolerance of luminous flux	+/-10%
optical data	
optical system	opal diffuser
material	aluminum
light emission	direct
light distribution	symmetrical

code	power [W]	luminaire power [W]	luminaire flux [lm]	luminaire efficacy [lm/W]	diameter [mm]	height [mm]	weight [kg]	box [mm]
E1041.K.C	31	34	3109	91	1410x44	56	2,3	1450x70x70

K-colour temperature

03 — 3000K

04 — 4000K

C-standard colour

03 — white

05 — black

06 — light grey

We reserve the right to withdraw and change products from the catalogue at any time without prior notice. The colour options presented in the catalogue may differ from the actual ones. Technical parameters are subject to change.

Liralighting Sp. zo. o. | ul. Saperów 4 | 82-300 Elbląg | info@liralighting.pl |tel. +48 55 236 11 85 | fax. +48 55 232 65 89 | www.liralighting.pl