ROLAND

Easy joy!

LIRALIGHTING

Luminaire with a simple, classic shape, designed as surface mounted. The luminaire body is made of steel, PMMA opal diffuser. General lighting fixture, available in three sizes. It is perfect for halls, public utility buildings, residential buildings and communication routes.

CE IP20







general data	
luminaire body	steel
mounting type	surface mounted
ingress protection IP	20
operation temperature range	from -40° to +30°
lifetime L80B10	50 000h
electrical data	
nominal voltage	220-240V AC
nominal frequency	50-60Hz
protection class	I
contains light source	yes
connection	connector through
dimming	none (options: DALI, Casambi)
lighting data	
light source	LED
colour rendering index	CRI>80
tolerance of luminous flux	+/-10%
optical data	
optical system	opal diffuser
material	PMMA
light emission	direct
light distribution	symmetrical

code	power [W]	luminaire power [W]	luminaire flux [lm]	luminaire efficacy [lm/W]	diameter [mm]	height [mm]	weight [kg]	box [mm]
E1001.K.C	13	13	540	42	200	100	0,9	220x220x120

K-colour temperature

03 3000K

04 4000K

C-standard colour

03 white

05 black

06 light grey

We reserve the right to withdraw and change products from the catalogue at any time without prior notice. The colour options presented in the catalogue may differ from the actual ones. Technical parameters are subject to change.

Liralighting Sp. zo. o. | ul. Saperów 4 | 82-300 Elbląg | info@liralighting.pl |tel. +48 55 236 11 85 | fax. +48 55 232 65 89 | www.liralighting.pl